Collider-Accelerator Department



Building 911B – P.O. Box 5000 Upton, NY 11973-5000 Phone 631 344 7124 Fax 631 344 5568 beavis@bnl.gov www.bnl.gov

managed by Brookhaven Science Associates for the U.S. Department of Energy

Memo

Date: March 26, 2015

To: RSC, H. Huang

From: D. Beavis & P. Bergh

Subject: Check-off list and Area Posting

The areas around the C-AD facility that have been posted as High Radiation Areas due to potential fault condition, are in the process of being surveyed and reposted as either Radiation Areas or Controlled Areas. Some of these areas may be inside existing posted Controlled or Radiation Areas. If this is the case for an area then the benefits of double posting will be evaluated by the RCD Representative.

This memorandum documents the surveys and running conditions for areas around the AGS ring. It has been sent to the LP for the AGS ring and the entire RSC to inform everyone that the surveys and reposting is in progress. When future areas are examined the documentation will be sent to the LP for the area and a copy to the RSC memo file but not distributed to the RSC. Members can always gain access to the documentation through the RSC memos folder online.

Areas that have potential radiation from the AGS ring had radiation surveys conducted during routine proton operations with polarizations protons on January 22, 2015 at about 10:30. The injected proton intensity was $3.5*10^{11}$ protons per cycle and the final accelerated intensity was $2.6*10^{11}$ protons per cycle. The areas that were surveyed were:

- Fan houses A,B,C,D,E
- HITL to AGS spur
- North west corner of the target building


The highest radiation level detected was 0.4 mrem/hr in the B fan house. Other areas were consistent with the minimum detectable level of 0.2 mrem/hr. The survey in the fan houses were conducted at the wall of the machinery housing. The distance from the housing to the duct is approximately eight feet. The machinery housing has two access ports which are labeled as confined spaces.


The surveys are filed in the HP archives, the chipmunk data relevant to the time period are attached in appendix I, and the present and proposed posting in Appendix II.


The fan houses and the northwest corner of the target building are inside an existing Radiation Area that encompasses most of the AGS ring and adjacent areas. These areas do not need to be explicitly posted as a Radiation Area unless the exterior posting is changed. All have the source of radiation as beam in the AGS ring.


The gates to the TtB tunnel are posted Radiation Area due operations of ion beam in the tunnel and not beam in the AGS ring. The radiation source of concern for the area inside the HITL spur gate is beam losses in the AGS ring. This gate should be explicitly posted as a Radiation Area to avoid circumstances where the TtB tunnel might be down posted since it is not operating with beam.

Appendix I: Chipmunk Data










Thu_Jan_22_2015_111401_27671.gif (PNG Image, 2172 \times 1229 pixels)

 $http://www.cadops.bnl.gov/elog/graphics/rhic-pp_2015/Thu_Jan_2$



Appendix II: Present and Proposed posting for the Areas

Revised Radiological Postings for Locked High Radiation Areas not protected by PASS. 3/26/15

Prior to down posting areas a routine dose rate survey will be performed.

Area	Current Posting	Proposed Posting	Comments
Fences around C14 and K7 escape Hatches	HIGH RADIATION AREA	RADIATION AREA W/ Beam On	Identified on RSC Safety Startup Check List If high intensity protons are run again this area would need to be posted High Radiation Area.
	CONTROLLED AREA RWP Required for Entry	CONTROLLED AREA Contact MCR for Beam Status	
		Access not Permitted With Beam on	
Fan House A,B,C, E Pad Locked Requires MCR Key, Access as per C-AD OPM 4.46	HIGH RADIATION AREA With Beam on CONTROLLED AREA RWP Required for Entry	RADIATION AREA CONTROLLED AREA RWP located in B911 Training office Follow C-AD OPM 4.46 for Access	Identified on RSC Safety Startup Check List *C-AD OPM 4.46 provides entry guidance
NW Corner of Exterior wall of Target Building	HIGH RADIATION AREA With Beam on CONTROLLED AREA	RADIATION AREA CONTROLLED AREA RWP located in B911	Identified on Safety Startup Check List * C-AD OPM 4.46

Pad Locked Requires MCR Key, Access as per C-AD OPM 4.46 V-Target Gate Double door, Pad lock, HP and MCR key	RWP Required for Entry HIGH RADIATION AREA	Training office Follow C-AD OPM 4.46 for Access RADIATION AREA CONTROLLED AREA RWP located in B911 Training office Follow C-AD OPM 4.63 for	Identified on RSC Safety Startup Check List **C-AD OPM 4.63 provides entry guidance
B914 Roof Security Fence Pad Locked Requires MCR Key, Access as per C-AD OPM 4.46	HIGH RADIATION AREA CONTROLLED AREA RWP Required for Entry	RADIATION AREA CONTROLLED AREA RWP located in B911 Training office Follow C-AD OPM 4.46 for Access	Identified on RSC Safety Startup Check List * C-AD OPM 4.46 provides entry guidance
In primary area at tunnel from HITL to AGS	HIGH RADIATION AREA W/ beam On	RADIATION AREA CONTROLLED AREA RWP located in B911	This area is within the PASS system. Survey will have to be done at a later date. Current posting needs to

		Training office Follow C-AD OPM 4.46 for Access	be verified.
Structure over C1 is posted to prohibit entry. No Door	Entry Prohibited	RADIATION BARRIER	Identified on RSC Safety Startup Check List
Top of B914 plug	HIGH RADIATION AREA	CAUTION	
door	CONTROLLED AREA RWP Required for Entry	ELEVATED WORK REQUIRES WORK PLANNING	Identified on RSC Safety Startup Check List
		Contact Liason Engineer or work planning manager for operational status and work planning.	This area is within the posted Radiation Area of B914.

^{*4.46} Procedure for Accessing the C-A Radiological Areas and Berms: AGS Ring Fan Houses (A,B,C,D and E), Northwest Corner of the Target Building, TANDEM/AGS ALCOVE, the Booster Berm/Bldg 914 Roof, the U-W (AtR) Berm, NSRL Berm, and the RHIC Berm During Accelerator Operation

^{**4.63} Accessing the Mothballed Vt and Vpri Areas